

| 电池特性 | | 电池照片 | | | | | | | | | |
|---|-------------------------|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 标称电压 | 6 V | | | | | | | | | | |
| 额定容量 | 260 Ah | | | | | | | | | | |
| 电池质量 (± 5%) | 46/101.4 kg/lbs | | | | | | | | | | |
| 外形尺寸 (± 1.5%) | | | | | | | | | | | |
| 长 | 356/13.98 mm/in. | | | | | | | | | | |
| 宽 | 180/7.17 mm/in. | | | | | | | | | | |
| 高 | 270/10.63 mm/in. | | | | | | | | | | |
| 总高 | 271/10.67 mm/in. | | | | | | | | | | |
| 质量比能量 | 33.9 Wh/kg | | | | | | | | | | |
| 体积比能量 | 90.2 Wh/cm ³ | | | | | | | | | | |
| 容量 (25°C, 77°F) | | 端子类型 M8×Φ18 | | | | | | | | | |
| 3hr (86.7A, 5.25V) | 260 Ah | | | | | | | | | | |
| 20hr (14.75A, 5.25V) | 295 Ah | | | | | | | | | | |
| 5hr (57A, 5.25V) | 285 Ah | | | | | | | | | | |
| 2hr (120A, 5.25V) | 240 Ah | | | | | | | | | | |
| 荷电态内阻 | 1.9 mΩ | | | | | | | | | | |
| 初充电电流 (推荐) | 35.0 A | | | | | | | | | | |
| 最大放电电流(10s) | 2340 A | | | | | | | | | | |
| 短路电流 | 5700 A | | | | | | | | | | |
| 浮充电压/单体 | 2.35 V | | | | | | | | | | |
| 均充电压/单体 | 2.45 V | | | | | | | | | | |
| 放电保持电压/单体 | 1.75 V | 端子材料: 铜 (镀锡) | | | | | | | | | |
| 80%循环寿命 | 700 次 | 扭 矩: 10~12N·m | | | | | | | | | |
| 100%循环寿命 | 400 次 | 产品执行标准: GB/T 32620.1-2016 电动道路车用铅酸蓄电池 | | | | | | | | | |
| | | 产品参考标准: IEC 61982-3-2001 | | | | | | | | | |
| 恒电流放电参数表 (at 25°C,77°F) —— 安 (A) | | | | | | | | | | | |
| 终止电压 (伏/单体) | 放电时间 (分钟) | | | | | | | | | | |
| | 10 | 20 | 30 | 45 | 60 | 90 | 120 | 180 | 300 | 600 | 1200 |
| 1.60 | 722.4 | 441.4 | 343.9 | 257.2 | 206.4 | 151.1 | 122.7 | 88.32 | 57.86 | 29.38 | 14.91 |
| 1.65 | 709.1 | 436.1 | 341.3 | 255.6 | 205.3 | 150.3 | 121.9 | 87.77 | 57.58 | 29.23 | 14.85 |
| 1.70 | 697.6 | 430.8 | 337.8 | 253.6 | 203.8 | 149.1 | 121.1 | 87.26 | 57.31 | 29.10 | 14.80 |
| 1.75 | 655.2 | 413.4 | 327.6 | 247.9 | 200.2 | 147.3 | 120.0 | 86.67 | 57.00 | 29.00 | 14.75 |
| 恒功率放电参数表 (at 25°C,77°F) —— 瓦特 (W) / 单体 | | | | | | | | | | | |
| 终止电压 (伏/单体) | 放电时间 (分钟) | | | | | | | | | | |
| | 10 | 20 | 30 | 45 | 60 | 90 | 120 | 180 | 300 | 600 | 1200 |
| 1.60 | 1277 | 800.3 | 636.2 | 483.2 | 392.2 | 290.4 | 238.5 | 172.7 | 113.7 | 58.07 | 29.59 |
| 1.65 | 1268 | 797.3 | 634.9 | 482.4 | 391.7 | 289.8 | 237.7 | 172.2 | 113.5 | 57.96 | 29.56 |
| 1.70 | 1261 | 794.0 | 633.1 | 481.6 | 390.7 | 288.7 | 236.7 | 171.7 | 113.3 | 57.90 | 29.55 |
| 1.75 | 1205 | 773.1 | 620.9 | 474.8 | 386.6 | 287.0 | 235.7 | 171.4 | 113.2 | 57.86 | 29.52 |

修订日期: 2017-01-22



备注: 厂家保留随时改进的权利, 恕不另行通知!